


6000 Series



wählen Anfrage NEIN.			Größe										Nennlast (N)		Gewicht (kg)
			D		D		B		Anfasen		Cr	Kor			
			mm	Zoll	mm	Zoll	Offener Typ	Geschirmter Typ	rsmin (r)						
										mm			Zoll	mm	
603	3	0.1181	9	0.3543	3	0.1181	5	0.1181	0.2	0.008	486	223	0.0014		
604	4	0.1575	12	0.4724	4	0.1575	4	0.1575	0.2	0.008	960	350	0.0023		
605	5	0.1969	14	0.5512	5	0.1969	5	0.1969	0.2	0.008	1070	420	0.0037		
606	6	0.2362	17	0.6693	6	0.2362	6	0.2362	0.3	0.012	1960	730	0.0069		
607	7	0.2756	19	0.748	6	0.2362	6	0.2362	0.3	0.012	2800	1060	0.0082		
608	8	0.315	22	0.8661	7	0.2756	7	0.2756	0.3	0.012	3290	1360	0.0129		
609	9	0.3543	24	0.9449	7	0.2756	7	0.2756	0.3	0.012	3330	1410	0.016		
6000	10	0.3937	26	1.0236	8	0.315	8	0.315	0.3	0.012	4160	1780	0.019		
6001	12	0.4724	28	1.1024	8	0.315	8	0.315	0.3	0.012	5110	2380	0.022		
6002	15	0.5906	32	1.2598	9	0.3543	9	0.3543	0.3	0.012	5590	2840	0.03		
6003	17	0.6693	35	1.378	10	0.3937	10	0.3937	0.3	0.012	6000	3250	0.039		
6004	20	0.7874	42	1.6535	12	0.4724	12	0.4724	0.6	0.024	9390	5020	0.069		
6005	25	0.9843	47	1.8504	12	0.4724	12	0.4724	0.6	0.024	10060	5860	0.08		
6006	30	1.1811	55	2.1654	13	0.5118	13	0.5118	1	0.039	11900	7460	0.116		
6007	35	1.378	62	2.4409	14	0.5512	14	0.5512	1	0.039	16210	10420	0.115		
6008	40	1.5748	68	2.6677	15	0.5906	15	0.5906	1	0.039	17030	11700	0.192		
6009	45	1.7717	75	2.9528	16	0.6299	16	0.6299	1	0.039	21080	14780	0.245		
6010	50	1.9685	80	3.1496	16	0.6299	16	0.6299	1	0.039	22000	16260	0.261		
60/22	22	0.8661	44	1.7323	12	0.4724	12	0.4724	0.6	0.024	9400	5050	0.074		
60/28	28	1.1024	52	2.0472	12	0.4724	12	0.4724	0.6	0.024	12500	7400	0.098		
60/32	32	1.2598	58	2.2835	13	0.5118	13	0.5118	1	0.039	15100	9150	0.129		