


GX..S



wählen	Anfrage	Bearing Number	Overall dimension [mm]												Rated load [kN]		Gewicht kg
			D	D	B	C	H	dk	S	d1 max	D1 min	A	rsr _{1s} min	a°	live load	Static load	
GX10S	10	30	7.5	7	9.5	32	7	27.5	15.5	3	0.6	5	27	136	0.036		
GX12S	12	35	9.5	9.3	13	38	8	32	18	4	0.6	5	37	188	0.072		
GX15S	15	42	11	10.8	15	46	10	39	22.5	5	0.6	6	53	267	0.108		
GX17S	17	47	11.8	11.2	16	52	11	43.5	27	5	0.6	4	61	311	0.137		
GX20S	20	55	14.5	13.8	20	60	12.5	50	31	6	1	5	84	425	0.246		
GX25S	25	62	16.5	16.7	22.5	68	14	58.5	34.5	6	1	5	134	672	0.415		
GX30S	30	75	19	19	26	82	17.5	70	42	8	1	5	182	909	0.614		
GX35S	35	90	22	20.7	28	98	22	84	50.5	8	1	5	266	1330	0.973		
GX40S	40	105	27	21.5	32	114	24.5	97	59	9	1	6	357	1810	1.59		
GX45S	45	120	31	25.5	36.5	128	27.5	110	67	11	1	6	486	2470	2.24		
GX50S	50	130	33	30.5	42.5	139	30	120	70	10	1	6	554	2810	3.14		
GX60S	60	150	37	34	45	160	35	140	84	12.5	1	6	748	3820	4.63		
GX70S	70	160	42	36.5	50	176	35	153	94.5	13.5	1	3	902	4610	5.37		
GX80S	80	180	43.5	38	50	197	42.5	172	107.5	14.5	1	4	1110	5700	6.91		
GX100S	100	210	51	46	59	222	45	198	127	15	1.1	4	1300	6470	11		
GX120S	120	230	53.5	50	64	250	52.5	220	145	16.5	1.1	3	1530	7580	14		
GX140S	140	260	61	54	72	274	52.5	243	177	23	1.5	3	1820	9040	19.1		
GX160S	160	290	66	58	77	313	65	271	200	23	1.5	2	2100	10440	25		
GX180S	180	320	74	62	86	340	67.5	299	225	26	1.5	4	2430	12070	32.8		
GX200S	200	340	80	66	87	365	70	320	247	27	1.5	1	3070	15280	35.4		